

FSI T25

Brochure

Stump Cutter for PTO 25-55 hp

FSI T25 is an ideal attachment for smaller tractors and similar machines with a PTO outlet.

The frame and 3-point linkage (cat. 1) ensure stability during grinding.

All movements are controlled via the joystick, the control box also has an option to adjust the speed of the swing movement.

Includes joystick control, PTO shaft and hydraulic top link.



Hydraulic

Tractor power requirement	19-41kW/25-55 hp
Oil flow	Max 35 l/min.
Oil pressure	Max. 150 bar
Hydraulic connections	Pressure + return
Hydraulic QR couplings	2 x 1/2"

PTO Speed	540 rpm
PTO with freewheel	Included

Cutting Head

Cutting disc diameter	470 mm
Tooth system	3 x turnable
Tooth diameter	20,5 mm
No of teeth's	18
Max cutting depth	41,5 mm
Cutting disc drive	V-belt system
Sweep	Hydraulic sweep

Cutting dimensions

Cutting height above ground	350 mm
Cutting depth below ground	400 mm
Cutting sweep width	1000 mm
Sweep speed	Adjustable

Hydraulic toplink	Included
-------------------	----------



FSI T25

Brochure

Stump Cutter for PTO 25-55 hp

Operator control

Joystick control Hydraulic

Measurements

Length 1750 mm
Width 1000 mm
Height 1100 mm
Weight 240 kg

Capacity by cutting

Average time for grinding stumps .

ø400 mm: 8 min.
ø650 mm: 15 min.
ø1050 mm: 50 min.

All based on figures from users grinding stumps 15 cm high to 15 cm below ground

